


ROSS-EMERGENCY Wall Light

MLWL416ANTBRS

Antique Brass







MATERIAL	Brass Glass
HEIGHT	26cm 10.24"
WIDTH DIAMETER	19.5cm 7.68"
LENGTH PROJECTION	15cm 5.91"
WEIGHT	2.9KG 6.39lbs
LAMPHOLDER	Integrated x 0
MAX WATTAGE	- x 0
VOLTAGE	220/240v or 110/120v
IP RATING	65
CLASS PROTECTION	II
SHADE	
FLEX BAR CHAIN LENGT	n/a
CABLE TYPE	

Fixing Bracket -

*For UL wired lights, fixing bracket may differ



Product Notes:

1) Lamps included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120 with the appropriate lampholders.






ROSS-EMERGENCY Wall Light

Antique Silver MLWL416ANTSLV







MATERIAL	Brass Glass
HEIGHT	26cm 10.24"
WIDTH DIAMETER	19.5cm 7.68"
LENGTH PROJECTION	15cm 5.91"
WEIGHT	2.9KG 6.39lbs
LAMPHOLDER	Integrated x 0
MAX WATTAGE	- x 0
VOLTAGE	220/240v or 110/120v
IP RATING	65
CLASS PROTECTION	II
SHADE	
FLEX BAR CHAIN LENGT	n/a
CABLE TYPE	

Fixing Bracket -

*For UL wired lights, fixing bracket may differ










ROSS-EMERGENCY Wall Light

MLWL416RAWBRS

Raw Brass







MATERIAL	Brass Glass
HEIGHT	26cm 10.24"
WIDTH DIAMETER	19.5cm 7.68"
LENGTH PROJECTION	14cm 5.51"
WEIGHT	2.9KG 6.39lbs
LAMPHOLDER	Integrated x 0
MAX WATTAGE	- x 0
VOLTAGE	220/240v or 110/120v
IP RATING	54
CLASS PROTECTION	II
SHADE	
FLEX BAR CHAIN LENGT	n/a
CABLE TYPE	-

Fixing Bracket -

*For UL wired lights, fixing bracket may differ



Product Notes:

1) Lamps included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120 with the appropriate lampholders.

